Canon

The imageCLASS™ 1100 Laser Multifunction System

Designed to do one thing today's businesses need.

EVERYTHING.

Whether you work in a small business, a home office, or an executive suite, it takes the right tools to be competitive. That's why you need the Canon imageCLASS 1100. In one affordable, space-saving device, you get the multifunction convenience of five separate machines — LASER PRINTER • LASER FAX • PC FAX • SCANNER • CONVENIENCE COPIER.

Equipped with Canon's MultiPASS™ Suite 3.11 for Windows® software, you'll be able to transmit documents from your PC as fast as 3 seconds per page*. And print them at 6 pages per minute with 600-dpi resolution†.

Backed by Canon's renowned quality and reliability, as well as a one-year warranty**, the imageCLASS 1100 provides an unparalleled combination of power, speed and productivity — the only thing you need for all of your business needs.

SUPER G3 FAXING
- 33.6 Kbps Super G3 Fax modem and JBIG Compression provide the fastest transmission speeds available (up to 3 seconds per page*)
- 40-sheet Automatic Document Feeder***
- 6-ppm print speed for incoming faxes
- Up to 256-page standard document memory▲

LASER PRINTING
- 6-ppm print speed
- 600-dpi resolution†
- 350-sheet total paper capacity:
  – 250-sheet letter cassette
  – 100-sheet MultiPurpose Tray
- FX-3 Single Cartridge (2,700-page yield††) included
- Face-down, Print-in-Order output
- Up to 6,000-page monthly print volume

MULTIPASS SUITE FOR WINDOWS®
- Canon MultiPASS Suite 3.11 for Windows® software bundled
- Windows® 95/98 and Windows NT® 4.0 compatible
- Fax, Print, Scan directly from any PC
- Provides "out-of-the-box" 5-in-1 multifunctionality

PC FAXING
- Send faxes from any PC at a fast, 3-second-per-page* Super G3 transmission speed
- Incoming faxes received confidentially in user's Electronic In-box
- View, Forward, Delete, Store, or Print faxes (same as E-mail)
- Large-capacity Electronic Address Book
- Fax Activity Log
- Customized Cover Sheet capability

SCANNING
- Scan text and images directly to your PC
- 600-dpi resolution
- 64-level grayscale
- TWAIN compatible

CONVENIENCE COPYING
- Makes up to 99 high-quality copies at a time
- Letter- , legal- , or A4-sized copies
- Convenient 40-sheet Automatic Document Feeder***
- 64-level grayscale

* Approximate 3-second-per-page fax transmission time based on ITU-T No. 1 Chart (MMR, Standard Mode) at 33.6 Kbps modem speed when transmitting to another V.34 machine. The Public Switched Telephone Network (PSTN) currently supports 28.8 Kbps modem speeds or lower, depending on telephone line conditions.
** One-year carry-in warranty.
*** Based on 20 lb. paper.
▲ Based on ITU-T No. 1 Chart (Standard Mode).
† Printing from PC using 600-dpi resolution setting lowers available fax memory to 60 pages. If fax memory currently in use exceeds 60 pages, 600 dpi cannot be utilized.
†† Based on 5% coverage.

PLAIN PAPER FAX

Type:	Desktop Transceiver
Applicable Line:	Public Switched Telephone Network
Compatibility:	G3
Data Compression:	MH, MR, MMR, JBIG
Modem Speed:	33.6/31.2/28.8/26.4/24.0/ 21.6/19.2/16.8/14.4/12.0/9.6/ 7.2/4.8/2.4 Kbps Automatic Fallback
Transmission Speed:	Approx. 3 Sec./Page*
Automatic Document Feeder:	40 Sheets LTR, 20 Sheets LGL**
Scanning Method:	Contact Image Sensor
Effective Scanning Width:	8.4" (214mm)
TX/RX Resolution	
Transmission:	203 dpi x 98 dpi, 203 dpi x 196 dpi, 203 dpi x 392 dpi, 406 dpi x 392 dpi
Reception:	203 dpi x 98 dpi, 203 dpi x 196 dpi, 203 dpi x 392 dpi, 406 dpi x 392 dpi
Printing:	600 dpi x 600 dpi
Enhanced Image Quality:	UHQ™ VI (Ultra High Quality) Auto Halftone Mode 64 shades of gray
Memory:	4MB (256 Pages***)
Memory Backup:	Standard (Approx. 1 hour)
Auto Dialing:	One-touch 24 Locations, Coded 100 Locations
FAX-TEL Auto Switch:	Standard (CNG Type)
Auto RX w/o Ring:	Standard
Answering Machine Hook-up:	Standard
Remote Reception:	Standard (Dialing Type)
Extension Phone Hook-up:	Standard
Manual 10-Key Dialing:	Standard
On-hook Key:	Standard
Auto Dialing:	124 Locations (Max Dial Digit 120, Average Digit 39)
Group Dialing:	123
Dial Search:	Standard

TRANSMISSION

Memory Transmission/ Reception:	Standard (Up to 256 Pages***)
Quick Memory Transmission:	Standard
Direct TX at Memory Full:	Standard
Dual Access:	Standard (Max. 20 Reservation)
TX Reservation:	Standard (Memory, Direct)
Interrupt Transmission:	Standard (Use Direct Transmission Key)
Polling Transmission:	Standard (Memory, ITU-T Mode)
Sequential Broadcasting:	Standard (Up to 125 Locations)
Delayed Transmission:	Standard (Up to 125 Locations, Up to 20 Preset Times)
Confidential Transmission:	Standard (ITU-T Mode)
Relay Broadcasting Command:	Standard (ITU-T Mode)
ITU-T Sub Address TX:	Standard (SUB/SEP/PWD)
Auto Redialing:	Standard 2 Times (1 - 15 Times), 2 Min. Interval (2 - 99 Min.)

RECEPTION

Memory Reception:	Standard (Auto Output, Up to 256 Pages***)
Polling Reception:	Standard
Transfer:	Standard (Timer)
Received Image Reduction:	Standard (Auto, Rate 70 - 100% in 1% increments)
Page Collation:	Standard (Face-down)
Activity Report:	Standard (Up to 20 Transactions)
Terminal ID:	Standard

PRINTER

Printing Method:	Laser Dry Electrostatic Transfer
Printing Resolution:	600 dpi x 600 dpi†
Printing Speed:	6 ppm
Recording Paper Supply:	250 Sheets LTR-sized Cassette 100 Sheets Adjustable MultiPurpose Tray (LTR/LGL/A4/EXE/B5/Custom)
Printer Driver:	Windows® GDI (Windows® 95/98, Windows NT® 4.0) (MultiPASS™ Driver)
Effective Printing Width:	8.2" (208mm)
Interface:	IEEE 1284 Parallel
Paper Output	
Paper Capacity:	Face-down: 50 Sheets
Toner Cartridge:	FX-3 Single Cartridge (2,700 pages, based on 5% coverage)

CONVENIENCE COPIER

Resolution:	Scan: 600 dpi x 600 dpi Print: 600 dpi x 600 dpi
Memory Copy:	Collate/Multiple Page Up to 99 Pages

PC-FAX

Multifunction Software:	Standard/MultiPASS Suite 3.11
PC Faxing:	TX/RX
Remote Setting:	Yes/Speed-dial, Date, TTI, TX/RX Setting
Support OS:	Windows NT® 4.0, Windows® 95/98
Address Book:	Yes
Import/Export:	Yes/Yes : CVS, TXT
Cover Page:	Yes
Incoming Fax to PC:	Yes
Send & Receive Resolution:	200 dpi x 100 dpi, 200 dpi x 200 dpi, 200 dpi x 400 dpi, 400 dpi x 400 dpi
Programming of Fax from PC:	Speed-dials · User Setting · Report Setting · TX Setting · RX Setting · Printer Setting · System Setting

SCANNER

Scanning Method:	B&W/Sheet Contact Image Sensor
Scanning Resolution:	Up to 600 dpi
Automatic Document Feeder:	40 Sheets LTR, 20 Sheets LGL**
Scanning Method:	CIS Contact Image Sensor
Document Sizes	
Minimum:	3.5" x 1.75"
Maximum:	8.5" x 39.0"
Viewer Software:	Yes/Scan Gear Editor
File Management Software:	Yes/MultiPASS Suite 3.11
Export File Format:	TIFF, PCX
Resolution:	200 dpi x 100 dpi, 200 dpi x 200 dpi, 200 dpi x 400 dpi, 300 dpi x 300 dpi, 400 dpi x 400 dpi, 600 dpi x 600 dpi
Grayscale:	256

REGULATIONS/ DIMENSIONS

Power Consumption	
Maximum:	Approx. 8W
Noise	
Standby:	30dB
Printing:	48dB
ENERGY STAR® Compliant:	Yes
Dimensions (H x W x D):	11.9" x 15.0" x 19.0" (303.5mm x 380mm x 483mm)
Weight:	28.7 lb. (13kg)

WARRANTY

One-year carry-in

Item #: imageCLASS 1100: H12 -1572-210
FX-3 Cartridge: H11-6381-230

---

* Approximate 3-second-per-page fax transmission time based on ITU-T No. 1 Chart (MMR, Standard Mode) at 33.6 Kbps modem speed when transmitting to another V.34 machine. The Public Switched Telephone Network (PSTN) currently supports 28.8 Kbps modem speeds or lower, depending on telephone line conditions.
** Based on 20 lb. paper.
*** Based on ITU-T No. 1 Chart (Standard Mode).
† Printing from PC using 600-dpi resolution setting lowers available fax memory to 60 pages. If fax memory currently in use exceeds 60 pages, 600 dpi cannot be utilized.

Canon KNOW HOW™

COPYTEX 1-800-832-7000
www.copytex.com

Canon U.S.A., Inc.
One Canon Plaza
Lake Success, NY 11042